

TYPE 3740 AND 3740XL

CARTRIDGE SPLIT SEALS



DESIGN BENEFITS


- Easy and fast installation
- > Factory pre-built assembly
- Pressure-balanced primary ring for increased pressure capability
- Reduces costly unscheduled outages
- > Extends operational life of your equipment

PRODUCT DESCRIPTION

We know the challenges you face in maintaining the reliability of your pumps and rotating shaft equipment. As a result, we developed the 3740 and 3740XL with your time, money, and man-power in mind. This wet-running split seal has been created for use in all cooling water, condensate vertical lift and wastewater pumps and equipment.

TYPE 3740 AND 3740XL

CARTRIDGE SPLIT SEALS



O-ring (Split)
Sealing Element O-ring
Mating Ring
Primary Ring
Set Screw
Spring Adapter
Assy. Set
Sealing Element
Gasket
Retaining Ring

Captive Socket Head Cap Crews

With increased reliability compared to traditional packing methods, John Crane's split seals are the answer. Without leakage from packing, bearing contamination and failure is significantly reduced, leading to increased equipment efficiency. Time-consuming packing adjustments are eliminated and lower frictional horsepower requirements reduce energy costs. The 3740XL can improve cost savings up to 66% over competitive split seals and 55% over packing.

Seal Type	Applications	Dry-running capability with large shaft run-out	Large Shaft Rotating Equipment (→ 6.000"/150mm)	Hard faces available for abrasive service	Suitable for field repair
3740	pumps			Х	X
3740D	pumps, mixers, agitators	X			X
3740XL	large pumps, mixers, agitators, screw feeders, water turbines		X	X	X

PERFORMANCE CAPABILITIES						
Seal Type	Pressure Limits	Speed Limits	Temperature Limits			
3740	Excursion 450 psi(g)/131 bar(g) Continuously 300 psi(g)/20.7 bar(g)	Up to 3500 fpm/17.8 m/s	Up to 250°F/121°C			
3740D	Vacuum to 80 psi(g)/5.5 bar(g)	400 fpm/2 m/s	275°F/135°C			
3740XL	Up to 200 psi(g)/13.8 bar(g)	Up to 3500fpm/17.8m/s	Up to 250°F/121°C			

Together, we will work with you to keep your mission-critical operations up and running, with support and guidance from our experienced team.



North America	Europe	Latin America	Middle East & Africa	Asia Pacific
United States of America	United Kingdom	Brazil	United Arab Emirates	Singapore
Tel: 1-847-967-2400	Tel: 44-1753-224000	Tel: 55-11-3371-2500	Tel: 971-481-27800	Tel: 65-6518-1800
Fax: 1-847-967-3915	Fax: 44-1753-224224	Fax: 55-11-3371-2599	Fax: 971-488-62830	Fax: 65-6518-1803

If the products featured will be used in a potentially dangerous and/or hazardous process, your John Crane representative should be consulted prior to their selection and use. In the interest of continuous development, John Crane Companies reserve the right to alter designs and specifications without prior notice. It is dangerous to smoke while handling products made from PTFE. Old and new PTFE products must not be incinerated. ISO 9001 and ISO 14001 Certified, details available on request.